

CLEANTECH 2000S



CleanTech 2000S Features

Ideal for food production, packaging, and cleanroom facilities in which consistent, guaranteed handwashing is critical for regulatory and standards compliance.

- Freestanding, stainless steel durable construction
- CIP model
- Self-clean cycle runs every 8 hours
- Optional Boot Sanitizing Pan, 23"x23"
- Optional Integrated Air Curtain Dryer (2000SA)

Dimensions

19" width x 21 1/2" depth x 48 1/2" height

Weight

98 lbs. (varies with options)

Shipping Weight

155 lbs. (varies with options)

Cycle and Activation

Automatic, via infrared photo-optical sensor
12-second wash and rinse cycle

Handwash Compliance Monitor

Counts number of handwash cycles
Optional resettable counter

Solutions Gauge

Indicates Normal/Empty/Blocked
Solution status

Water Consumption

0.6 gallons per hand wash cycle

Self-Cleaning Feature

The handwashing system self-cleans 3x times per day (once per shift).

Electrical

System: 100-250 VAC, 50/60 Hz, 300 W
Optional Air Dryer: 120 VAC, 50/60 Hz, 2000 W

Plumbing

2 each, 3/4" male hose, hot and cold minimum 4 GPM,
40-80 PSI, 60 PSI optimum

Drain

Standard 1 1/5" drain stub
P-Trap to be supplied by facility
Ideal drain height 18-22" from floor

Solutions Storage

2 - One gallon containers of Hand Soap
1 - One gallon container of Self-Clean

Solutions

Required solutions provided by Meritech
(Other solutions will void warranty)



meritech.com • 800.932.7707

CleanTech Automated Handwashing and Bootwashing Systems are protected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.