

# CLEANTECH 4000S



## CleanTech 4000S Features

Ideal for food production, food processing, packaging, and cleanroom facilities that require large throughput and where consistent, effective handwashing is critical for regulatory and standards compliance.

- 3-Bay, freestanding, stainless steel durable construction
- Self-clean cycle runs every 8 hours
- One drain and one water line
- Optional Boot Sanitizing Pan, 23" x 23"
- Optional Integrated Air Curtain Dryer (4000SA)

## Dimensions

56" width x 21 1/2" depth x 48 1/2" height

## Weight

294 lbs. (varies with options)

## Shipping Weight

500 lbs. (varies with options)

## Cycle and Activation

Automatic, via infrared photo-optical sensor  
12-second wash and rinse cycle

## Handwash Compliance Monitor

Counts number of handwash cycles  
Optional resettable counter

## Solutions Gauge

Indicates Normal/Empty/Blocked  
Solution status

## Water Consumption

0.6 gallons per hand wash cycle

## Self-Cleaning Feature

The handwashing system self-cleans 3x times per day (once per shift).

## Electrical

System: 100-250 VAC, 50/60 Hz, 300 W per station  
Optional Air Dryer: 120 VAC, 50/60 Hz, 2000 W per station

## Plumbing

2 each, 3/4" male hose, hot and cold minimum 4 GPM,  
40-80 PSI, 60 PSI optimum

## Drain

Standard 1 1/5" drain stub  
P-Trap to be supplied by facility  
Ideal drain height 18-22" from floor

## Solutions Storage

2 - One gallon containers of Hand Soap in each bay  
1 - One gallon container of Self-Clean in each bay

## Solutions

Required solutions provided by Meritech  
(Other solutions will void warranty)



meritech.com • 800.932.7707

CleanTech Automated Handwashing and Bootwashing Systems are protected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.