

CLEANTECH 500EZ



CleanTech 500EZ Features

When durability and CIP is desired for food processing, packaging, or food service industries, this 500EZ is the most economical option — same technology but less features than our larger models.

- Designed for high-use areas
- Wall mount
- Washes up to elbows
- Stainless steel body, NEMA 4X electronics housing
- Optional Integrated Air Curtain Dryer (500EZA)

Dimensions

17 1/4" width x 15 3/4" depth x 22 1/2" height

Weight

62 lbs.

Shipping Weight

72 lbs.

Cycle and Activation

Automatic, via infrared photo-optical sensor
12-second wash and rinse cycle

Handwash Compliance Monitor

Counts number of handwash cycles
Optional resettable counter

Solutions Gauge

Indicates Normal/Empty/Blocked
Solution status

Water Consumption

0.6 gallons per hand wash cycle

Electrical

100-250 VAC 50/60 Hz, 300 W

Plumbing

2 each, 3/4" male hose, hot and cold minimum 4 GPM,
40-80 PSI, 60 PSI optimum

Drain

Standard 1 1/2" drain stub
P-Trap to be supplied by facility
Ideal drain height 18-22" from floor

Solutions Storage

3 - One gallon containers of Hand Soap

Solutions

Required solutions provided by Meritech
(Other solutions will void warranty)



meritech.com • 800.932.7707

CleanTech Automated Handwashing and Bootwashing Systems are protected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.